
Data sheet

valid from: 1/8/21





Schedule 80 CORZAN® CPVC Plain End Pipe - 20 Ft Lengths

- Max Water Pressure at 73°F (22.7°C) with solvent-cemented joints

Size (inch)	P/L	Plain End Code	Lift Qty (ft)	Average O.D. (inch)	min. wall (inch)	Wt/Ft (lbs/ft)	Max Water Pressure (psi)
¼	H06	**H0800025CG2000**	5700	0.540	0.119	0.112	1130
⅜	H06	**H0800038CG2000**	5700	0.675	0.126	0.154	920
½	H06	**H0800050CG2000**	5700	0.840	0.147	0.225	850
¾	H06	**H0800075CG2000**	5260	1.050	0.154	0.305	690
1	H06	**H0800100CG2000**	4280	1.315	0.179	0.449	630
1 ¼	H06	**H0800125CG2000**	2360	1.660	0.191	0.618	520
1 ½	H06	**H0800150CG2000**	2060	1.900	0.200	0.751	470
2	H06	**H0800200CG2000**	1660	2.375	0.218	1.040	400
2 ½	H06	**H0800250CG2000**	1080	2.875	0.276	1.584	420
3	H06	**H0800300CG2000**	840	3.500	0.300	2.124	370
3 ½	H06	**H0800350CG2000**	680	4.000	0.318	2.607	350
4	H06	**H0800400CG2000**	520	4.500	0.337	3.105	320
5	H06	**H0800500CG2000**	400	5.563	0.375	4.343	290
6	H06	**H0800600CG2000**	340	6.625	0.432	5.929	280
8	H06	**H0800800CG2000**	220	8.625	0.500	9.051	250
10	H06	**H0801000CG2000**	80	10.750	0.593	13.429	230
12	H06	**H0801200CG2000**	60	12.750	0.687	18.458	230
14	H06	**H0801400CG2000**	60	14.000	0.750	22.224	220
16	H06	**H0801600CG2000**	60	16.000	0.843	28.557	220
18	H06	**H0801800CG2000**	40	18.000	0.937	35.745	220
20	H06	**H0802000CG2000**	40	20.000	1.031	45.022	220
24	H06	**H0802400CG2000**	40	24.000	1.218	63.878	210

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
Phone +41 -(0)52-631 1111
e-mail: info.ps@georgfischer.com
Internet: http://www.gfps.com