




Fabricated bend 11,25°

Curva 11,25° por sectores
 Courbe 11,25° à secteurs
 segmentierter Bogen 11,25°


Manufactured by welding of pipe segments
 Fabricado mediante soldadura de segmentos de tubo
 Fabriqué par soudage de segments de tuyau
 Produziert durch Schweißung von Rohrstücken (segmentgeschweißt)

PN6 SDR26




dn	code	H [mm]	Z [mm]	Weight [kg]
355	CS1125P355A.2	300	315	-
400	CS1125P400A.2	300	320	-
450	CS1125P450A.2	300	320	-
500	CS1125P500A.2	300	325	-
560	CS1125P560A.2	350	380	-
630	CS1125P630A.2	350	380	-

PN10 SDR17



dn	code	H [mm]	Z [mm]	Weight [kg]
355	CS1125P355B.2	300	315	-
400	CS1125P400B.2	300	320	-
450	CS1125P450B.2	300	320	-
500	CS1125P500B.2	300	325	-
560	CS1125P560B.2	350	380	-
630	CS1125P630B.2	350	380	-

PN16 SDR11



dn	code	H [mm]	Z [mm]	Weight [kg]
355	CS1125P355C.2	300	315	-
400	CS1125P400C.2	300	320	-
450	CS1125P450C.2	300	320	-
500	CS1125P500C.2	300	325	-
560	CS1125P560C.2	350	380	-
630	CS1125P630C.2	350	380	-